

5010/5080 LED Aimer
5110/5180 High Visibility LED Aimer
5310/5380 Laser Aimer
Decoded Miniature Image Engines



Features

Powered by Adaptus™ Imaging Technology - The world's finest technology for data collection. Adaptus Imaging Technology delivers superior value through versatility and performance and embodies Hand Held Products continuous commitment to leading technology, superior solutions, and helping business customers solve their data capture problems.

Point-and-Shoot Scanning Ease of Use - Available in high visibility LED and laser aimer versions, these omni-directional area imagers make reading linear and full matrix codes quick and easy with industry-leading motion tolerance, low light sensitivity, and broad depth of reading distances.

Durable - Designed with industrial grade image sensor technology and no moving parts, these imagers can withstand rugged applications and sub-zero freezing temperatures.

Decoding - Built on a 30-year old tradition of decoding expertise, these decoded out engines will read all major linear, stacked linear, and matrix bar codes, as well as machine-readable OCR fonts, quickly and easily.

Fifth Generation Image Processing - Based on a history of applying image-based technology to reading bar codes, these engines bring a legacy of industry-leading image processing performance. In addition to reading bar codes well, these products also capture crisp digital images for use in your data collection system.

The 5000 family combines the latest CMOS industrial grade image sensor technology, illumination, and optics to create a compact, light-weight optical module capable of reading linear, stacked linear, and matrix bar codes like never before. In addition, these images can read and decode OCR fonts and capture digital images.


This fifth generation of image engines build on the Hand Held Products legacy of reading the most comprehensive list of bar code symbologies and combine with value add image capture and OCR reading capability. Hand Held Products has a long history of supplying OEM devices to the bar code reading industry. Our commitment to applying image-based processing innovation to traditional bar code applications enables us to help ease your transition to image-based readers. In addition, our partnership friendly culture and sensitivity to life cycle management helps you manage your engine integration and evolution to ensure your devices always have the latest and best technology available.

Designed for ease-of-integration and superior durability, the 5X10/5X80 decoded engines are ideal as drop-in modules to most data capture applications. The small size and low current draw of the devices allow the engines to be integrated with minimal mechanical modifications. Incorporating sensor technology with no moving parts, the 5X10/5X80 Series engines are built to withstand 2,500G of shock. The decoder module supports standard serial and USB interfaces that, in most cases, does not require hardware modifications to existing platforms.

These full omni-directional readers are available in configurations to meet your integration needs. Several focal distances, mounting options, aiming ergonomics, and decoder license configurations are available. These options enable integrators to design in the benefits of image capture into a wide variety of devices, including bar code scanners, hand held mobile computers, medical instrumentation, diagnostic equipment, gaming terminals, vending machines, and robotics.

To learn how the 5X10/5X80 Series engines can work for you, contact us at any of the locations listed on the back or visit us at www.handheld.com.

5X10/5X80 Series Specifications



Performance

Focal Point

SR: 7 inches (17.8cm) from lens plate
 SF: 4.5 inches (11.4cm) from lens plate

SR Working Range:*

	8.3 mil Linear (.020cm)	10 mil PDF417 (.025cm)	13 mil UPC (.033cm)	15 mil Data Matrix (.038cm)	15 mil QR (.038cm)	35 mil MaxiCode (.089cm)
Near	3.5 in. (8.9cm)	3.1 in. (7.9cm)	2.1 in. (5.3cm)	2.3 in. (5.8cm)	3.1 in. (7.9cm)	2.0 in. (5.1cm)
Far	7.6 in. (19.3cm)	9 in. (22.9cm)	13.2 in. (33.5cm)	10.2 in. (25.9cm)	8.8 in. (22.4cm)	13.0 in. (33cm)

SF Working Range:*

	6.6 mil PDF417 (.017cm)	7.5 mil Linear (.019cm)	8.3 mil Data Matrix (.021cm)	8.3 mil QR (.021cm)	10 mil Linear (.025cm)	13 mil UPC (.033cm)
Near	2.8 in. (7.1cm)	2.5 in. (6.4cm)	3.4 in. (8.6cm)	3.4 in. (8.6cm)	2.2 in. (5.6cm)	2.0 in. (5.1cm)
Far	6 in. (15.2cm)	6.5 in. (16.5cm)	5.7 in. (14.5cm)	5.4 in. (13.7cm)	7.6 in. (19.3cm)	8.9 in. (22.6cm)

*Data characterized at 23°C and 0 lux ambient light

Image Sensor:

752 x 480 CMOS sensor

Motion Tolerance:

4 inches per second

Rotational Sensitivity:

360°

Viewing Angle:

±40°

Ambient Light:

Total darkness to 100,000 lux (full sunlight)

Illumination

Illumination LEDs: 626nm ±30nm

Aiming

LEDs: 526nm ±30nm

Laser: 650nm ±10nm

Symbologies

2 Dimensional:

PDF417, MicroPDF417, MaxiCode, Data Matrix, QR Code, Aztec, Aztec Mesa, Code 49, UCC Composite

Linear:

Code 39, Code 128, Codabar, UPC, EAN, Interleaved 2 of 5, Reduced Space Symbology, Code 93, Codablock

Postal:

Postnet (US), Planet Code, BPO 4 State, Canadian Post, Japanese Post, KIX (Netherlands) Post

OCR Fonts:

OCR-A and OCR-B

Mechanical Specifications

	5010/5080	5110/5180	5310/5380	5010/5080	5110/80, 5310/80	Decoder
	Image Module	Image Module	Image Module	Bracketed Device	Bracketed Device	Board
Depth:	.584 in. (14.83mm)	.564 in. (16.74mm)	.7 in. (1.78cm)	.982 in. (24.94mm)	1.11 in. (28.19mm)	1.51 in. (38.35mm)
Width:	.83 in. (21.08mm)	1.1 in. (27.94mm)	1.1 in. (2.79cm)	1.51 in. (38.35mm)	1.51 in. (38.35mm)	.86 in. (22.8mm)
Height:	.47 in. (11.94mm)	.45 in. (11.43mm)	.475 in. (1.21cm)	.765 in. (19.43mm)	.765 in. (19.43mm)	.357 in. (9.07mm)
Weight:	1 ounce (28.3g)	1 ounce (28.3g)	1 ounce (28.3g)	1 ounce (28.3g)	1 ounce (28.3g)	

Electrical Specifications

Operational Input Voltage

Imager: 3.3 VDC ± 5% (23° C)

5X10/5X80: 3.0 VDC to 5.5 VDC (23° C)

Current Draw

Imager: Maximum Operating Current – 100 mA, Standby Current – 100 µA

	Average Current*	Standby Current	Peak	
5X10/5X80:	510 mA	120 uA	600 mA	*Interlaced Mode

Environmental Specifications

Temperature Ranges

Operating: -30° to +50° C (-22° to 122° F)

Storage: -40° to +70° C (-40° to 158° F)

Humidity:

up to 95% RH, non-condensing at 122°F (50° C)

Shock:

18 shocks of 2,500 G

Worldwide Offices

Offices Serving North America
 Skaneateles Falls, NY
 Tel: +1 315 685 8945
 or, in North America: +1 800 582 4263
 napresales@handheld.com
 Charlotte, NC
 Tel: +1 704 998 3998
 or, in North America: +1 800 582 4263
 napresales@handheld.com

Offices Serving Europe, Middle East, and Africa
 Europe
 Tel: +31 (0) 40 29 01 600
 eupresales@handheld.com
 United Kingdom
 Tel: +44 (0) 1 925 240055
 eupresales@handheld.com
 Italy
 Tel: +39 (0) 2 67 100752
 eupresales@handheld.com

France
 Tel: +33 (0) 1 41 158220
 eupresales@handheld.com
 Germany
 Tel: +49 (0) 7 477 151377
 eupresales@handheld.com
 Spain
 Tel: +34 93 228 78 68
 eupresales@handheld.com

Offices Serving Asia and the Pacific Rim
 Hong Kong
 Tel: +852 2511 3050
 appresales@handheld.com
 Japan
 Tel: +813 5770 6312
 appresales@handheld.com
 Shanghai
 Tel: +86 21 6361 3818
 appresales@handheld.com

Offices Serving Latin America
 Naples, Florida
 Tel: +1 239 263 7600
 lapresales@handheld.com
 São Paulo
 Tel: +55 11 2178 0500
 lapresales@handheld.com
 Rio De Janeiro
 Tel: +55 21 2178 0500
 lapresales@handheld.com
 Mexico
 Tel: +52 55 5203 2100
 lapresales@handheld.com

Web Site Address www.handheld.com

Hand Held Products, Inc., ("Hand Held Products") © 1999-2005. All rights reserved. Printed in the U.S.A.

Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.